

5501LT 55-inch

Touchscreen Signage





Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The 5501LT Interactive Digital Signage display combines an infrared multi- touch touchscreen with a professional- grade, large format display in a slim, integrated package. The 5501LT offers system integrators and value-added resellers (VARs) a high performance solution that is easy to deploy and maintain. With a total thickness of 3.4 inches (87mm), the 5501LT is compliant with the ADA requirement of less than 4" protrusion for wall-mounted products when used with a compatible wall-mount.

With a 500 nit LED panel, the 5501LT is a bright, high quality display suitable for public environments. The infrared touchscreen enables up to ten simultaneous touches for multi-user interaction. The touchscreen is 4mm thick with fully tempered glass.

Thin (<4" mounted) design is attractive and compliant with ADA and IBC protrusion requirements

Reliable, integrated IDS solution with optional NFC / RFID scanners and webcam kits

Flexible mounting in portrait, landscape and table-top orientation

5501LT 55" Touchscreen Signage

Specifications					
Model	5501LT				
Form Factor	Digital Signage				
Bezel Color	Black				
Active Display Area (W x H)	47.6" x 26.8" (1210mm x 680mm)				
Dimensions (W x D x H)	49.9" x 3.4" x 29.1" (1267mm x 87mm x 738mm)				
LCD Technology	Active matrix TFT LCD with LED backlight				
Mounting Options*	VESA 4-hole mount per MIS-F, 600, 600, 6MM				
Display Technology	Full HD 1920 x 1080 (native) active matrix TFT LCD with LED backlight; 1073.7m colors; 16:9 aspect ratio. Other resolutions supported				
Aspect Ratio	16:9				
Number of Colors	1073.7 million				
Brightness (typical)	LCD Panel 500 nits; with Infrared 450 nits				
Response Time (Tr + Tf) (typical)	6.5 ms				
Viewing Angle (typical)	Horizontal: ±89°; Vertical: ±89°				
Contrast Ratio (typical)	4000:1				
Video Inputs	Video Analog VGA on Female DE-15 connector; HDCP-capable HDMI 1.3 on Type A connector; DisplayPort 1.1a connector; Input Video Horizontal Sync frequency range: 31.5-73KHz; Input Video Vertical Sync (frame rate) frequency range: 47-63Hz				
Power	Input power connector: IEC 60320 C14; Input power signal specifications: 100-240VAC 50/60Hz; Monitor Only - Power Consumption: (typical at 120V at 60Hz): ON: 122W; SLEEP: 10W; OFF: 2W; Monitor Only - Power Consumption: (typical at 230V at 50Hz): ON: 119W; SLEEP: 9W; OFF: 1.5W;				
Audio	Internal Speakers: 4 x 5W stereo speakers; Input audio connector: 3.5mm TRS jack; Input audio signal range: 1Vrms max stereo signal (standard PC line out); Headphone output connector: 3.5mm TRS jack				
Weight	Unpackaged: with ECMG2B: 103.2 lbs (46.8kg); without ECMG2B: 98.9 lbs (44.9kg); Packaged: with ECMG2B: 123.8 lbs (56.2kg); without ECMG2B: 119.4 lbs (54.2kg)				
Shipping Dimensions	Width: 55.9" (1420mm); Height: 34.6" (880mm); Depth: 9.2" (235mm)				
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 140°F (-20°C to 50°C)				
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95%				
Regulatory Approvals and Declarations	UL, FCC; cUL, IC; CB; CE				
Accessories	NFC Adapter (E918074), OPS Kit (E102270), OSD Control Box (E483757) Replacement Cable Kit (E000263), Wall Mount Kit (E248743), Webcam (E688656)				
Warranty	3 year standard (worldwide) with on-site exchange (NA only). 2 year extended warranty option available (NA and EMEA only).				
MTBF	50,000 hours demonstrated				
What's in the box	HDMI cable, USB cable, North America power cable, EU/KR power cable, UK power cable, AR power cable, CH power cable, JP power cable, 3-pin to 2-pin adapter for JP power cable, VGA+RS232 Y-cable, VGA cable, 3.5mm Audio cable, energy label according to EU Regulation 1062/2010				

Ordering Information

Model	Part Number	Technology	Color
5501LT	E268254	Infrared (up to 10 touches)	Black

Optional Computer Modules

Model	Part Number	Processor	RAM	Storage	OS
ECMG2B-i3	E001292	Intel Core 4th Gen i3 3.4 GHz HD4400	2GB	320GB	No OS
	E001293	Intel Core 4th Gen i3 3.4 GHz HD4400	2GB	320GB	Windows 7
	E001294	Intel Core 4th Gen i3 3.4 GHz HD4400	2GB	320GB	Windows 8.1
ECMG2B-i5	E001295	Intel Core 4th Gen i5 3.7 GHz HD4600	4GB	320GB	No OS
	E001296	Intel Core 4th Gen i5 3.7 GHz HD4600	4GB	320GB	Windows 7
	E001297	Intel Core 4th Gen i5 3.7 GHz HD4600	4GB	320GB	Windows 8.1
ECMG2B-i7	E001298	Intel Core 4th Gen i7 4.0 GHz HD4600	8GB	320GB	No OS
	E001299	Intel Core 4th Gen i7 4.0 GHz HD4600	8GB	320GB	Windows 7
	E001300	Intel Core 4th Gen i7 4.0 GHz HD4600	8GB	320GB	Windows 8.1
AECM ECMG2	E000739	Qualcomm Snapdragon APQ8064 CPU	2GB	16 GB eMMC	Android

To find out more about our extensive range of Elo touch solutions, go to **elotouch.com**, or call the office nearest you.

North America
Tel +1 408 597 8000
Fax +1 408 597 8050
customerservice@elotouch.com

EuropeTel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-PacificTel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America Tel 786-923-0251 Fax 305-931-0124 www.elotouch.com



