

4 CH AHD DVR

SA-4100AHD-2L (MM)

1080P Lite



MODEL		SA-4100AHD-2L(MM)	
System	Compression Format	High profile H.264	
	ONVIF	Yes (For IP Channels)	
	Format	AHD / CVBS	
Video	Input	4CH Standard BNC	
	Standard Output	HDMI, VGA (800x600, 1024x768, 1280x1024)	
Audio	Input	1CH	
	Output	1CH	
	Two Way Audio	Yes	
Recording	AHD	Real-Time Recording	4CH 1080P Lite Real-Time
		2MP (1080P)	No
		2MPL (1080P Lite)	120FPS (NTSC)/100FPS (PAL)
		1MP (720P)	120FPS (NTSC)/100FPS (PAL)
	Analog	Real-Time Recording	4CH 960H Real-Time
		960H	120FPS (NTSC)/100FPS (PAL)
		D1	No
		CIF	No
	IP	Real-Time Recording	No
		3MP	No
		2MP (1080P)	No
		1.3MP (960P)	No
		1MP (720P)	No
General	Recording Modes	Schedule, Manual, Motion	
Playback	AHD/TVI/CVBS Playback	4CH	
	IP Playback	No	
	Search Mode	Time, Event, File Management	
Backup	USB	2 USB 2.0 Port	
	DVD Burner	No	
	Backup Format	AVI/DAT	
Remote Application	AHD Stream	Master Stream 1-25/30FPS@1080P Lite; Sub-Stream 1-12/15@CIF	
	Analog Stream	Master Stream 1-25/30FPS@960H; Sub-Stream 1-12/15@CIF	
	IP Stream	No	
	Master Stream	Up to 4CH@Recording Resolution	
	Browser	IE, Safari, Firefox (Mac OS, Windows XP/Vista/7/8/10)	
	CMS	Yes	
	Mobile Application	Provision Cam2 for iOS/Android	
	User Access	10 Users Online with Professional Authority Management	
Alarm	Input	No	
	Output	No	
Storage	HDD	1 SATA (6TB)	
	E-SATA	No	
PTZ	Connection	RS-485 / CoC	
	Supported Protocols	Pelco D, Pelco P, Samsung, Visca, CoC	
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus	
Network	Ethernet	100 Mbps (RJ-45)	
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P	
Others	Dimension	W255xD200xH43mm	
	IR Controller	Yes	
	Power Supply	12V/2A	
	Operation Temperature	0°C ~50°C	